



The Model K-200, K-300 and K-400 thickness gauges are provided with a swing-out foot for on-table operation.

Specifications	K-15	K-50	K-50-2	K-50-3	K-50-5	K-100	K-200	K-300	K-400
Resolution:	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm	0.1 mm
Measuring range:	10 mm	10 mm	20 mm	30 mm	50 mm	30 mm	30 mm	30 mm	30 mm
Depth of jaws:	15 mm	50 mm	50 mm	50 mm	50 mm	100 mm	200 mm	300 mm	400 mm
Scale diameter:	36 mm	54 mm	54 mm	54 mm	54 mm	54 mm	54 mm	54 mm	54 mm
Measuring pressure:							1.8 N	1.8 N	1.8 N
On request:							0.9/2.5 N	0.9/2.5 N	0.9/2.5 N
Feeler shape*:	f	a/b/c/d/e	a/b/c/d/e	a/b/c/d/e	a/b/c/d/e	a/b/c/d/e	a/b/c/d/e	a/b/c/d/e	a/b/c/d/e
Spring force:	●	●	●	●	●	●			
Lifting device:							○	○	○
Weight, net:	60 g	300 g	300 g	330 g	350 g	450 g	700 g	1000 g	1400 g

* To order, please indicate the desired feeler, e.g. K-50-B for gauge with feeler »b«.

Subject to change without notice.